

REVISIONS			
REV	DESCRIPTION	DATE	BY

Material: PET

Flammability: UL 224 VW-1

Operating temperature: -50°C~150° C / Intermittent 220°C

Tensile Strenght: 100,000 PSI


Colour: black and grey

Halogen free

All dimensions are in mm



<i>P/N Black</i>	<i>P/N Grey</i>	<i>Nominal diameter</i>	<i>Minimal diameter</i>	<i>Maximal diameter</i>	<i>PKG. MT.</i>
8053PT01	8053PT11	3,0	1,0	5,0	200
8054PT01	8054PT11	4,0	2,0	7,0	200
8055PT01	8055PT11	5,0	3,0	8,0	100
8051PT01	8051PT11	6,0	3,0	9,0	200
8056PT01	8056PT11	8,0	5,0	12,0	100
8060PT01	8060PT11	10,0	7,0	15,0	100
8061PT01	8061PT11	12,0	6,0	20,0	100
8062PT01	8062PT11	15,0	8,0	23,0	100
8063PT01	8063PT11	20,0	12,0	30,0	100
8065PT01	8065PT11	25,0	18,0	34,0	50
8066PT01	8066PT11	30,0	20,0	40,0	50
8067PT01	8067PT11	40,0	25,0	60,0	50
8070PT01	8070PT11	50,0	45,0	75,0	25

		TITLE EXPANDABLE BRAIDED SLEEVING	
		MATERIAL SEE ABOVE	DATE 28/05/2019
PART NUMBER SEE TABLE		DRAWN R.F.	
DRAWING NUMBER 19.05.28.80XX.0.E		CHECK	
SIZE A4	SCALE NTS	COLOR SEE ABOVE	APPROVED
UNIT mm.	REV A	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	