



REVISIONS			
REV	DESCRIPTION	DATE	BY



P/N	As supplied: inside diameter (min.)	After recovery: inside diameter (max.)	After recovery: wall thickness (min.)	Bars length mt
14348RA01	12,0	3,0	1,8	1,22
14349RA01	16,0	5,0	2,1	1,22
14350RA01	22,0	6,0	2,4	1,22
14351RA01	33,0	8,0	2,6	1,22
14352RA01	40,0	12,0	2,6	1,22
14353RA01	55,0	16,0	2,7	1,22
14354RA01	65,0	19,0	2,9	1,22
14355RA01	75,0	22,0	3,0	1,22
14356RA01	95,0	25,0	3,6	1,22
14357RA01	115,0	34,0	3,5	1,22
14358RA01	140,0	42,0	3,3	1,22
14359RA01	160,0	50,0	3,3	1,22
14360RA01	180,0	58,0	3,3	1,22
14361RA01	265,0	75,0	3,8	1,22
14362RA01	300,0	75,0	3,8	1,22
13188RA01	350,0	100,0	4,3	1,22

Notes:

Colour: Black
Medium-wall tubing without hot melt adhesive
Material: Crosslinked Polyolefin
Shrink ratio: 3:1
Good environmental protection
Ideal for low voltage applications

UV resistant
Operating temperature: -55 °C +110 °C
Minimum full recovery temperature: +120 °C
Longitudinal change 0 ± 10% massimo
All dimensions are in mm

				TITLE MEDIUM-WALL HEAT SHRINK TUBING			
				MATERIAL SEE ABOVE		DATE 24/04/2020	
						DRAWN R.F.	
PART NUMBER SEE TABLE		DRAWING NUMBER 20.04.24.14XXX.0.E		COLOR SEE ABOVE			
SIZE A4	SCALE NTS	UNIT mm.	REV A	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE			
				CHECK 			
				APPROVED 			