



REVISIONS			
REV	DESCRIPTION	DATE	BY



P/N	As supplied: inside diameter (min.)	After recovery: inside diameter (max.)	After recovery: wall thickness (min.)	Bars length mt
14363RA01	9,0	3,0	1,95	1,22
14364RA01	15,0	4,0	2,35	1,22
14365RA01	20,0	6,0	2,45	1,22
14366RA01	33,0	8,0	3,15	1,22
14367RA01	43,0	12,0	4,05	1,22
14368RA01	51,0	16,0	4,05	1,22
14369RA01	75,0	22,0	4,2	1,22
14370RA01	235,0	65,0	4,1	1,22
14371RA01	265,0	75,0	4,3	1,22

**Notes:**

**Colour: Black**  
**Material: Polyolefin**  
 Superior electrical and environmental insulation  
 Excellent abrasion and impact resistance  
 Ideal for low voltage applications  
 UV resistant

**Operating temperature: -55 °C +110 °C**  
**Minimum shrink temperature: +120 °C**  
**Longitudinal change 0 ± 10% max.**  
**\*Also available in lengths of 1 and 1,5 meter**  
**All dimensions are in mm**

				TITLE <b>HEAVY-WALL HEAT SHRINK TUBING</b>	
				MATERIAL SEE ABOVE	DATE 24/04/2020
PART NUMBER SEE TABLE				DRAWN R.F.	
				DRAWING NUMBER 20.04.24.143XX.0.E	
SIZE A4				COLOR SEE ABOVE	
				CHECK	
SCALE NTS		UNIT mm.		UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	
REV A		APPROVED			