



| REVISIONS | | | |
|-----------|-------------|------|----|
| REV | DESCRIPTION | DATE | BY |
| | | | |
| | | | |



| P/N | As supplied: inside diameter (min.) | After recovery: inside diameter (max.) | After recovery: wall thickness (min.) | Reel / Meter |
|-----------|-------------------------------------|--|---------------------------------------|--------------|
| 14397FK01 | 3,2 | 1,6 | 0,80 | 50 |
| 14398FK01 | 4,8 | 2,4 | 0,95 | 50 |
| 14399FK01 | 6,4 | 3,2 | 0,98 | 50 |
| 14400FK01 | 9,5 | 4,8 | 1,00 | 50 |
| 14401FK01 | 12,7 | 6,4 | 1,16 | 30 |
| 14402FK01 | 19,0 | 9,5 | 1,49 | 30 |
| 14403FK01 | 25,4 | 12,7 | 1,85 | 30 |

Notes:

Colour: Black

Material: FKM (Viton) Fluoroelastomer tubing

Shrink ratio: 2:1

Flammability: UL224 VW-1

Superior abrasion resistance

High temperature resistance


Excellent resistance to aggressive chemicals and solvents

Operating temperature: -40 °C +200 °C

Minimum full recovery temperature: +175 °C

Longitudinal change 0 ± 10% max.

All dimensions are in mm

| | | | | | |
|---|--|--------------|--|---|--|
|  | | | | TITLE HEAT SHRINK TUBING 2:1 RESISTANT 200° | |
| | | | | MATERIAL SEE ABOVE | |
| PART NUMBER SEE TABLE | | | | DRAWING NUMBER 20.04.24.14XXX.0.E | |
| | | | | DRAWN R.F. | |
| SIZE A4 | | SCALE NTS | | UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE | |
| UNIT mm. | | REV A | | APPROVED | |