



REVISIONS			
REV	DESCRIPTION	DATE	BY



P/N	As supplied: inside diameter (min.)	After recovery: inside diameter (max.)	After recovery: wall thickness (min.)	Bars length mt
15983RA01	12,0	3,0	2,0	1,22
14333RA01	16,0	4,0	2,4	1,22
14334RA01	24,0	6,0	2,6	1,22
14335RA01	34,0	8,0	3,2	1,22
14336RA01	48,0	12,0	4,0	1,22
14337RA01	55,0	16,0	4,0	1,22
14338RA01	75,0	22,0	4,0	1,22
14339RA01	95,0	25,0	4,0	1,22
14340RA01	130,0	35,0	4,2	1,22
14342RA01	160,0	50,0	4,2	1,22
14343RA01	180,0	50,0	4,2	1,22
14344RA01	200,0	60,0	4,2	1,22
14345RA01	235,0	65,0	4,4	1,22
14346RA01	265,0	75,0	4,8	1,22

**Notes:**

**Colour: Black**

**Material: Polyolefin**

**Superior electrical and environmental insulation**

**Excellent abrasion and impact resistance**

**Ideal for low voltage applications**

**UV resistant**

**Operating temperature: -55 °C +110 °C**

**Minimum shrink temperature: +120 °C**

**Longitudinal change 0 ± 10% max.**

**\*Also available in lengths of 1 and 1,5 meter**

**All dimensions are in mm**

				TITLE <b>HEAVY-WALL HEAT SHRINK TUBING WITH ADHESIVE</b>	
				MATERIAL SEE ABOVE	DATE 24/04/2020
PART NUMBER SEE TABLE				DRAWN R.F.	
				DRAWING NUMBER 20.04.24.143XX.0.E	
SIZE A4				COLOR SEE ABOVE	
				CHECK	
SCALE NTS		UNIT mm.		UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	
REV A		APPROVED			