

DIM.	TOL.
5mm DOWN	±0.2
5~20mm	±0.3
20~40mm	±0.4
40~60mm	±0.5
60~100mm	±0.8
100mm UP	±1.0

REVISIONS			
REV	DESCRIPTION	DATE	BY

P/N	A	B	C	SIZE	HOLE	THICKNESS	COLOUR	Ø CABLE
12292GS019005	20,0	12,7	5,4	M12	M12	2,0-5,0	RAL 9005	4,0-7,0
12292GS117001	20,0	12,7	5,4	M12	M12	2,0-5,0	RAL 7001	4,0-7,0
12292GS117035	20,0	12,7	5,4	M12	M12	2,0-5,0	RAL 7035	4,0-7,0
12293GS019005	21,0	18,0	10,5	M16	M16	2,0-5,0	RAL 9005	5,0-9,0
12293GS117001	21,0	18,0	10,5	M16	M16	2,0-5,0	RAL 7001	5,0-9,0
12293GS117035	21,0	18,0	10,5	M16	M16	2,0-5,0	RAL 7035	5,0-9,0
12294GS019005	22,0	40,0	28,9	M63	M63	1,0 - 4,0	RAL 9005	34,0 - 45,0
12294GS117001	22,0	34,8	25,0	M63	M63	1,0 - 4,0	RAL 7001	34,0 - 45,0
12294GS117035	22,0	40,0	28,9	M63	M63	1,0 - 4,0	RAL 7035	34,0 - 45,0

		TITLE	
		METRIC SNAP-FIT PROTECTION GROMMETS	
		MATERIAL	DATE
		EPDM	19/04/2017
			DRAWN
			R.F.
PART NUMBER		DRAWING NUMBER	COLOR
		17.04.19.12292.0.E	GREY RAL 7035
SIZE	SCALE	UNIT	REV
A4	NTS	mm	A
		UNLESS OTHERWISE SPECIFIED TOLERANCE	
		SEE ABOVE	
APPROVED			