



REVISIONS			
REV	DESCRIPTION	DATE	BY



P/N	As supplied: inside diameter (min.)	After recovery: inside diameter (max.)	After recovery: wall thickness (min.)	Reel / Meter
14240RA01	1,6	0,5	0,45	150
14241RA01	3,2	1,1	0,50	150
14242RA01	4,8	1,6	0,6	75
14243RA01	6,4	2,1	0,65	75
14244RA01	9,5	3,2	0,75	50
14245RA01	12,7	4,2	0,80	30
14246RA01	19,1	6,4	0,90	30
14247RA01	25,4	8,5	1,0	30
14248RA01	39,0	13,0	1,20	30

**Notes:**

**Colour: Black**

**Material: FKM (Viton) Fluoroelastomer tubing**

**Shrink ratio: 3:1**

**Flammability: UL224 VW-1**

**Superior abrasion resistance**

**High temperature resistance**


**Excellent resistance to aggressive chemicals and solvents**

**Operating temperature: -55 °C +125 °C**

**Minimum full recovery temperature: +100 °C**

**Longitudinal change 0 ± 10% max.**

**All dimensions are in mm**

				TITLE <b>HEAT SHRINK TUBING 3:1 RESISTANT 125°</b>	
				MATERIAL CROSSLINKED POLYOLEFIN	
PART NUMBER SEE TABLE				DRAWING NUMBER 22.05.24.14XXX.0.E	
				COLOR BLACK	
SIZE A4	SCALE NTS	UNIT mm.	REV A	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	
				APPROVED	