




REVISIONS			
REV	DESCRIPTION	DATE	BY



P/N	As supplied: inside diameter (min.)	After recovery: inside diameter (max.)	After recovery: wall thickness (min.)	Reel / Meter
14268RA01	1,6	0,5	0,45	150
14269RA01	3,2	1,1	0,5	150
14270RA01	4,8	1,6	0,6	75
14271RA01	6,4	2,1	0,65	75
14272RA01	9,5	3,2	0,75	75
14273RA01	12,7	4,2	0,8	50
14274RA01	19,1	6,4	0,9	30
14275RA01	25,4	8,5	1,2	30
14276RA01	39,0	13,0	1,25	30

Notes:
Colour: Black
Material: Reticulated polyolefin
Shrink ratio: 3:1
Flammability: UL224 VW-1
Superior abrasion resistance
High temperature resistance
Excellent resistance to aggressive chemicals and solvents
Operating temperature: -55 °C +135 °C
Minimum full recovery temperature: +100 °C
Longitudinal change 0 ± 10% max.
All dimensions are in mm

				TITLE HEAT SHRINK TUBING 3:1 RESISTANT 135°	
				MATERIAL SEE ABOVE	
PART NUMBER SEE TABLE				DRAWING NUMBER 22.05.20.14XXX.0.E	
				DRAWN A.C.	
SIZE A4		SCALE NTS		UNIT mm.	
REV A		UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE		APPROVED	